# ROLLON 100

Premium Mobility Chair. Folds in seconds. Fits in any car













**ROLLON BEARINGS PVT. LTD.**

7 Mile, Kanakapura Road, Bangalore 560062

T +91 98455 04526 / +91 98451 63412 E info@rollon100.com www.rollon100.com

## SET UP UPON ARRIVAL

I. Unfold the footrest (P1).
II. Grab the push handle and the frame, and push them to opposite sides (P2). Listen for a "click" sound, which indicates that the lock is engaged.
III. Push down the armrest (P3).




P1




P2




P3

## ADJUST THE PUSH HANDLE

I. Turn the knob counterclockwise to loosen (P4).
II. Rotate the push handle and turn it to face the back (P5).
III. Then turn the knob clockwise to tighten the push handle (P5).
Should you need to use it as a walker, rotate the push handle to face forward.




P4




P5

## USING THE SEAT BELT

I. Fasten the seat belt (P6).
II. Adjust the seat belt length (P7).
III. Pull the adjustment buckle down to remove any extra loop (P8).



P6



P7



P8

## SEAT STRAP ADJUSTMENT

The seat cushion is detachable. There are five straps underneath that support the user's weight. The tightness of each strap can be adjusted based on the user's preference for best comfort.





## BRAKE AND LOCK

I. To engage the brake: Hold the brake handle up to 3/4 of the way to apply the brake (P9).
II. To lock the brake: Hold the brake handle up all the way; the lock will engage (P9).
III. To release the lock: Pull the small lever located under the brake handle upwards (P10).



P9



P10

## FOLDING THE WHEELCHAIR

1. Prepare the wheelchair: Pull up the armrest (P11). Pull the lock to unlock and push the backrest slightly forward. Simultaneously, you can step on the bar between the rear wheels to stabilize the wheelchair and prevent it from moving (P12).
2. Fold the wheelchair: Hold the backrest, lift the seat frame upward (P13), and fold the foot rest (P14)




P11




P12




P13




P14